



26m Diesel Scissor



MACHINE SPECIFICATION SHEET

S80D

| | |
|--------------------|------------|
| REACH HEIGHT | 26.50m |
| PLATFORM HEIGHT | 24.50m |
| CLOSED LENGTH | 5.74m |
| CLOSED HEIGHT | 4.20m |
| CLOSED WIDTH | 2.50m |
| PLATFORM EXTENSION | 1.81m |
| LIFTING CAPACITY | 750kg |
| WEIGHT | 16,300kg |
| CAGE DIMENSIONS | 2.50x5.35m |
| MINIMUM HEIGHT* | 3.16m |
| IPAF CATEGORY | 3a |
| POWER | DIESEL |

| | |
|----------------|-------------------|
| FEATURED MODEL | JLG LIFTLUX LL245 |
|----------------|-------------------|

The JLG LIFTLUX LL245 rough terrain diesel scissor offers a range of features:

- Four wheel drive
- A lifting capacity of 750kg
- Large working platform offers flexibility for operators and materials
- Self-levelling outriggers making it an ideal choice for a wide range of power stations, construction, maintenance work in large warehouses and industrial plants

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification.

*Minimum height reference to stowed height with guardrails down where applicable.

