



# 23m Electric Spider Lift

## MACHINE SPECIFICATION SHEET

### TR23L

REACH HEIGHT	23.00m
PLATFORM HEIGHT	21.00m
CLOSED LENGTH	5.50m
CLOSED HEIGHT	2.10m
CLOSED WIDTH	0.78m
HORIZONTAL REACH	12.40m
WIDTH MAX WORKING	3.55m
WIDTH MIN WORKING	2.95m
SAFE WORKING LOAD	200kg
WEIGHT	2,865kg
CAGE DIMENSIONS	1.40x0.70x1.10m
GRADEABILITY	31%
CAGE ROTATION	180°
IPAF CATEGORY	1b
SLEW	360°
UP AND OVER CLEARANCE	8.75m
MINIMUM SETUP AREA	2.65x5.33m (WxL)
TRACK SURFACE AREA	N/A
DRIVE SPEED	2.00km/h
MAXIMUM SETUP INCLINE	31%
NO. OUTRIGGER POSITIONS	Multi 4*
POWER	ELECTRIC
FEATURED MODEL	CMC 23



The S23 model is the latest designed platform featuring great performance which expresses the best of all CMC's experience and technological capabilities. It is a platform with double pantograph and telescopic boom and jib, designed and manufactured to give the maximum in operational performance, versatility of use and transportability. The excellent balance between weight, strength and working height makes it the most compact platform with the longest outreach in its class. Equipped with the Self Control System by CMC for automatic control of stabilisation, manoeuvring speed, automatic closure of the aerial part and collision prevention.

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification. Variable jacking will envelope. Outreach is variable depending on load, angle of rotation and outrigger configuration.

\*Narrow, standard, left side, right side.

