



26m Hybrid Spider Lift

MACHINE SPECIFICATION SHEET

TR26H

REACH HEIGHT	26.00m
PLATFORM HEIGHT	24.00m
CLOSED LENGTH	5.58m
CLOSED HEIGHT	1.98m
CLOSED WIDTH	0.99m
HORIZONTAL REACH	14.50m
WIDTH MAX WORKING	3.30m
WIDTH MIN WORKING	2.50m
SAFE WORKING LOAD	250kg
WEIGHT	3,350kg
CAGE DIMENSIONS	1.30x0.70x1.10m
GRADEABILITY	28% (16°)
CAGE ROTATION	124° (+/-62°)
IPAF CATEGORY	1b
SLEW	340°
UP AND OVER CLEARANCE	9.2m
MINIMUM SETUP AREA	4.30x4.44m (WxL)
TRACK SURFACE AREA	N/A
DRIVE SPEED	N/A
MAXIMUM SETUP INCLINE	28.7% (11°)
NO. OUTRIGGER POSITIONS	3
POWER	HYBRID
FEATURED MODEL	BLUELIFT 26M HYBRID



The Bluelift Hybrid are well known for their compact and lightweight hybrid tracked access platforms. the SA26 makes no exception, at 5.58M in length this 26M platform is smaller than some 22M spiderlifts.

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification. Variable jacking will envelope. Outreach is variable depending on load, angle of rotation and outrigger configuration.

