



30m Diesel/Mains Spider Lift

MACHINE SPECIFICATION SHEET

TR30P

REACH HEIGHT	30.00m
PLATFORM HEIGHT	28.00m
CLOSED LENGTH	7.20m
CLOSED HEIGHT	1.98m
CLOSED WIDTH	1.58m
HORIZONTAL REACH (300 Kg Basket)	14.00m
WIDTH MAX WORKING	4.75m
WIDTH MIN WORKING	2.99m
SAFE WORKING LOAD	400kg
WEIGHT	4,500kg
CAGE DIMENSIONS (Standard Basket)	1.20x0.80x1.10m
GRADEABILITY	16.70°/30.0%
CAGE ROTATION	180°
IPAF CATEGORY	1b
SLEW	360°
UP AND OVER CLEARANCE	N/A
MINIMUM SETUP AREA	1.58 X 7.55 (WxL)
MAXIMUM SETUP WIDTH	1.92 X 0.25 m
TRACK SURFACE AREA	5.6 X 5.51m
DRIVE SPEED	3km/hour
MAXIMUM SETUP INCLINE	30% (16.7°)
NO. OUTRIGGER POSITIONS	3
POWER	DIESEL/ MAINS
FEATURED MODEL	TEUPEN 30T PLUS



The Teupen Leo 30T Plus has a lifting capacity of 200KG, this machine is also available with a lifting attachment capable of lifting up to 450KG.

The Teupen has hydraulically adjustable tracks and variable jacking allowing this machine to work on rough terrains or indoors on delicate flooring with width restrictions.

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification. Variable jacking will envelope. Outreach is variable depending on load, angle of rotation and outrigger configuration.

