



56m Truck Mount

MACHINE SPECIFICATION SHEET

TM56

REACH HEIGHT	56.00m
PLATFORM HEIGHT	54.00m
CLOSED LENGTH	11.98m
CLOSED HEIGHT	3.80m
CLOSED WIDTH	2.50m
HORIZONTAL REACH	39m
WIDTH MAX WORKING	9.0m
WIDTH MIN WORKING*	3.0m
SAFE WORKING LOAD	600kg
WEIGHT	26,000kg
CAGE DIMENSIONS	1.10 x 2.40 x 1.10m (2.40 extends to 3.70m)
CAGE ROTATION	2 x 90°
IPAF CATEGORY	1b
SLEW	540°
FEATURED MODEL	Bronto S56XR

WILSON ACCESS HIRE

The Bronto Skylift S56XR is an industry-leading truck-mounted platform designed for extreme reach and high-capacity performance. It boasts a massive 56.00m working height and an exceptional 39.00m horizontal outreach, offering unparalleled access for the most demanding projects.

Equipped with variable jacking and automatic levelling, the S56XR ensures maximum stability and precision even on challenging sites. The heavy-duty cage provides a maximum load of 600kg, accommodating a large team with equipment, while the Sky Jib offers flexible "up and over" positioning. Ideally suited for wind turbine maintenance, high-rise glazing, and complex industrial installations, this machine features Bronto Compass remote diagnostics for peak reliability.

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification. Variable jacking will effect the working envelope. Outreach is variable depending on load, angle of rotation and outrigger configuration.

